

# Model name

## P18EN UL2 (Outdoor unit) / P18EN NSK (Indoor unit)

Function (indicate if present)	
cooling	Y
heating	Y

If the function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.

Average (mandatory)	Y
Warmer (if designated)	N
Colder (if designated)	N

Item	symbol	value	unit
<b>Design load</b>			
cooling	Pdesignc	5,0	kW
heating / Average	Pdesignh	3,9	kW
heating / Warmer	Pdesignh	x,x	kW
heating / Colder	Pdesignh	x,x	kW

Item	symbol	value	unit
<b>Seasonal efficiency</b>			
cooling	SEER	6,5	-
heating / Average	SCOP/A	4,0	-
heating / Warmer	SCOP/W	x,x	-
heating / Colder	SCOP/C	x,x	-

Declared capacity* for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	Pdc	5,00	kW
Tj=30°C	Pdc	3,75	kW
Tj=25°C	Pdc	2,49	kW
Tj=20°C	Pdc	1,34	kW

Declared Energy efficiency ratio* for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	EERd	3,25	-
Tj=30°C	EERd	4,49	-
Tj=25°C	EERd	7,55	-
Tj=20°C	EERd	14,10	-

Declared capacity* for heating / Average climate, at indoor temperature 20°C and outdoor temperature Td			
Tj=-7°C	Pdh	3,45	kW
Tj=2°C	Pdh	2,10	kW
Tj=7°C	Pdh	1,35	kW
Tj=12°C	Pdh	1,32	kW
Tj=bivalent temperature	Pdh	3,60	kW
Tj=operating limit	Pdh	3,90	kW

Declared Coefficient of performance* for heating / Average climate, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	2,84	-
Tj=2°C	COPd	3,93	-
Tj=7°C	COPd	4,91	-
Tj=12°C	COPd	6,14	-
Tj=bivalent temperature	COPd	2,95	-
Tj=operating limit	COPd	2,60	-

Declared capacity* for heating / Warmer climate, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	Pdh	x,x	kW
Tj=7°C	Pdh	x,x	kW
Tj=12°C	Pdh	x,x	kW
Tj=bivalent temperature	Pdh	x,x	kW
Tj=operating limit	Pdh	x,x	kW

Declared Coefficient of performance* / Warmer climate, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	COPd	x,x	-
Tj=7°C	COPd	x,x	-
Tj=12°C	COPd	x,x	-
Tj=bivalent temperature	COPd	x,x	-
Tj=operating limit	COPd	x,x	-

Declared capacity* for heating / Colder climate, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	x,x	kW
Tj=2°C	Pdh	x,x	kW
Tj=7°C	Pdh	x,x	kW
Tj=12°C	Pdh	x,x	kW
Tj=bivalent temperature	Pdh	x,x	kW
Tj=operating limit	Pdh	x,x	kW
Tj=-15°C	Pdh	x,x	kW

Declared Coefficient of performance* / Colder climate, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	x,x	-
Tj=2°C	COPd	x,x	-
Tj=7°C	COPd	x,x	-
Tj=12°C	COPd	x,x	-
Tj=bivalent temperature	COPd	x,x	-
Tj=operating limit	COPd	x,x	-
Tj=-15°C	COPd	x,x	-

Bivalent temperature			
heating / Average	Tbiv	-8	°C
heating / Warmer	Tbiv	x	°C
heating / Colder	Tbiv	x	°C

Operating limit temperature			
heating / Average	Tol	-10	°C
heating / Warmer	Tol	x	°C
heating / Colder	Tol	x	°C

Cycling interval capacity			
for cooling	Pcycc	x,x	kW
for heating	Pcyh	x,x	kW

Cycling interval efficiency			
for cooling	EERcyc	x,x	-
for heating	COPcyc	x,x	-

Degradation cooling**	co-efficient Cdc	0,25	-
-----------------------	------------------	------	---

Degradation heating**	co-efficient Cdh	0,25	-
-----------------------	------------------	------	---

Electric power input in power modes other than 'active mode'			
off mode	P <sub>OFF</sub>	0,002	kW
standby mode	P <sub>SB</sub>	0,002	kW
thermostat-off mode	P <sub>TO</sub>	0,020	kW
crankcase heater mode	P <sub>CK</sub>	0	kW

Annual electricity consumption			
cooling	Q <sub>CE</sub>	269	kWh/a
heating / Average	Q <sub>HE</sub>	1365	kWh/a
heating / Warmer	Q <sub>HE</sub>	xx	kWh/a
heating / Colder	Q <sub>HE</sub>	xx	kWh/a

Capacity control (indicate one of three options)	
fixed	N
staged	N
variable	Y

Other items			
Sound power level (indoor/outdoor)	L <sub>WA</sub>	60 / 65	dB(A)
Global warming potential	GWP	2087.5	kgCO <sub>2</sub> eq.
Rated air flow (indoor/outdoor)	-	1080 / 2100	m <sup>3</sup> /h

Contact details for obtaining more information: **Christianna PAPAZHARIOU**, Internal communicator - Energy & environment regulations expert, LG Electronics, Paris Nord II - 117 avenue des Nations, BP 59372 Villepinte - 95942 Roissy CDG Cedex, chris.papazahariou@lge.com, Tel. +33 1 49 89 57 41, +33 6 83 077 455



\*= For staged capacity units, two values divided by a slash (/) will be declared in each box in the section "Declared capacity of the unit" and "declared EER/COP" of the unit.  
 \*\*= If default Cd=0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating or cooling cycling test value is required.