



# ENERG

енергия · ενεργεια

Y IJA  
IE IA



Model Indoor unit **MSZ-FT35VG**  
Outdoor unit **MUZ-FT35VGHZ**

SEER



A<sup>+++</sup>

A<sup>+++</sup>

A<sup>++</sup>

A<sup>+</sup>

A

B

C

D

kW 3,5

SEER 8,6

kWh/annum 142

SCOP



A<sup>+++</sup>

A<sup>+++</sup>

A<sup>++</sup>

A<sup>++</sup>

A<sup>+</sup>

A

A

B

C

D

kW 2,2

4,0

5,9

SCOP 5,8

4,6

3,5

kWh/annum 527

1216

3453



60dB



61dB



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI  
626/2011

JG79Y746H02



Model	Indoor unit	MSZ-FT25VG MSZ-FT25VGHZ	MSZ-FT35VG MSZ-FT35VGHZ	MSZ-FT50VG MSZ-FT50VGHZ	
	Outdoor unit	MUZ-FT25VGHZ	MUZ-FT35VGHZ	MUZ-FT50VGHZ	
Sound power levels on cooling mode	Inside dB	60	60	60	
	Out-side dB	60	61	64	
Refrigerant R32 GWP 675 *1					
Cooling	SEER	8,6	8,6	7,2	
	Energy efficiency class	A+++	A+++	A++	
	Annual electricity consumption *2 kWh/a	101	142	243	
	Design load kW	2,5	3,5	5,0	
Heating (Average / Warmer / Colder season)	SCOP	4,6 / 5,8 / 3,5	4,6 / 5,8 / 3,5	4,3 / 5,5 / 3,3	
	Energy efficiency class	A++ / A+++ / A	A++ / A+++ / A	A+ / A+++ / B	
	Annual electricity consumption *2 kWh/a	973 / 432 / 2766	1216 / 527 / 3453	1625 / 684 / 4707	
	Design load kW	3,2 / 1,8 / 4,7	4,0 / 2,2 / 5,9	5,0 / 2,7 / 7,4	
	De-clared capacity	at reference de-sign temperature kW	3,2(-10°C) / 1,8(2°C) / 3,1(-22°C)	4,0(-10°C) / 2,2(2°C) / 3,7(-22°C)	5,0(-10°C) / 2,7(2°C) / 4,0(-22°C)
	at bivalent temperature kW	3,2(-10°C) / 1,8(2°C) / 3,2(-10°C)	4,0(-10°C) / 2,2(2°C) / 4,0(-10°C)	5,0(-10°C) / 2,7(2°C) / 5,0(-10°C)	
at operation limit temperature kW	3,0(-25°C) / 3,0(-25°C) / 3,0(-25°C)	3,4(-25°C) / 3,4(-25°C) / 3,4(-25°C)	3,6(-25°C) / 3,6(-25°C) / 3,6(-25°C)		
Back up heating capacity kW	0,0(-10°C) / 0,0(2°C) / 1,6(-22°C)	0,0(-10°C) / 0,0(2°C) / 2,2(-22°C)	0,0(-10°C) / 0,0(2°C) / 3,4(-22°C)		

Deutsch	Italiano	Svenska	Polski	Eesti	Malti	Русский
Français	Ελληνικά	Česky	Slovensko	Gaeilge	Suomi	Norsk
Nederlands	Português	Slovensky	Slovensko	Latviski	Türkçe	Українська
Español	Dansk	Magyar	Română	Lietuvių k.	Hrvatski	
Modell	Modèllo	Modell	Model	Mudel	Mudell	Модель
Modèle	Μοντέλο	Model	Model	Déanamh	Malli	Modell
Model	Modelo	Model	Model	Modelis	Model	Модель
Modelo	Model	Modell	Model	Modelis	Model	Модель
Innengerät	Unità interna	Inomhusenhet	Jednostka wewnętrzna	Siseseade	Unità għal gewwa	Внутренний прибор
Appareil intérieur	Εσωτερική μονάδα	Vnitřní jednotka	Notranja enota	Aonad laistigh	Sisäyksikkö	Innendørsenhet
Binnenunit	Unidade interior	Vnútorná jednotka	Вътрешно тяло	Iekšējais ierīce	İç ünite	Внутрішній блок
Unidad interior	Indendørsenhet	Beltéri egység	Unitate de interior	Patalpoje montuojamas įrenginys	Unutarnja jedinica	
Außengerät	Unità esterna	Utomhusenhet	Jednostka zewnętrzna	Välisseade	Unità għal barra	Наружный прибор
Modèle extérieur	Εξωτερική μονάδα	Vnější jednotka	Zunanja enota	Aonad lasmuigh	Ulkoyksikkö	Utendørsenhet
Buitenunit	Unidade exterior	Vonkajšia jednotka	Външно тяло	Ārtelpas ierīce	Diş ünite	Зовнішній блок
Unidad exterior	Udenørsenhet	Kültéri egység	Unitate de exterior	Lauke montuojamas įrenginys	Vanjska jedinica	
Schalleistungspegel im Kühlmodus	Livelli di potenza sonora in modalità di raffreddamento	Bullernivå i nedkylningsläget	Poziom mocu dźwięku w trybie chłodzenia	Müratasemed jahutusrežiimis	Livelli tal-qawwa tal-hsejjes fil-modalità tat-tkessih	Значения уровня звуковой мощности в режиме охлаждения
Niveaux de puissance corrects en mode de refroidissement	Επίπεδα ισχύος ήχου στην κατάσταση ψύξης	Úrovně hluchnosti v režimu chlazení	Ravni zvonoči moči v načinu hlajenje	Leibhèil chumhachta fuaimhe ar mhodh fuairthe	Äänvoimakkuustasot viilennystilassa	Lydytkäiväer i avkylingsmodus
Geluidsniveaus in koelstand	Níveis de potência sonora em modo de arrefecimento	Hladiny akustického výkonu v režime chladienia	Нива на звуковата мощност в режим на охлаждане	Akustiskās jaušanas līmenis dzesēšanas režīmā	Soğutma modunda ses gücü düzeyleri	Рівні звукової потужності у режимі охолодження
Niveles de potencia del sonido en el modo de refrigeración	Lydstyrkeniveauer i kølefunktion	Hangnyomászintek hűtés üzemmódban	Level sonor in modul de răcire	Garso galios lygis vėsimo režimu	Razine zvučnog tlaka pri hladenju	
Innen	Interno	Insida	Wewnętrz	Sees	Gewwa	Внутри
À l'intérieur	Εσωτερικό	Uvnitř	Znotraj	Laistigh	Sisäpuoli	Innendig
Binnenkant	Interior	Vo vnutri	Вътре	Iekšējais pats	İç taraf	Усередини
Interior	Indvendig	Bent	Interior	Vidinis	Unutra	
Außen	Esterno	Utsida	Na zewnątrz	Väljas	Barra	Снаружи
À l'extérieur	Εξωτερικό	Venku	Zunaj	Lasmuigh	Ulkopuoli	Utvendig
Buitenkant	Exterior	Vonku	На открито	Ārtelpā	Diş taraf	Назовні
Exterior	Udvendig	A szabadban	Exterior	Išorinis	Vani	
Kühlmittel	Refrigerante	Köldmedel	Czynnik chłodniczy	Külmutusagens	Refrigerant	Хладагент
Réfrigérant	Ψυκτικό	Chladivo	Hladidlo sredstvo	Cuisneán	Kylmäaine	Κρυομεδיום
Koelmiddel	Refrigerante	Chladivo	Хладилен агент	Aukstumaģents	Soğutucu	Холодоагент
Refrigerante	Kølemiddel	Hűtőközeg	Refrigerent	Saldama	Rashladno sredstvo	

Deutsch	Italiano	Svenska	Polski	Eesti	Malti	Русский	
Français	Ελληνικά	Česky	Slovensko	Gaeilge	Suomi	Norsk	
Nederlands	Português	Slovensky	Slovensko	Latviski	Türkçe	Українська	
Español	Dansk	Magyar	Română	Lietuvių k.	Hrvatski		
Kühlen	Raffreddamento	Kyla	Chłodzenie	Jahutus	Tkessiħ	Охлаждение	
Refrroidissement	Ψύξη	Chlazení	Hlajenje	Fuarú	Viilennys	Avkjøling	
Koelen	Arrefecimento	Chladienia	Охлаждане	Dzesēšana	Soğutma	Охлаждження	
Refrigeración	Køling	Hűtés	Răcire	Vėsiniimas	Hladenje		
Energieeffizienzklasse	Classe di efficienza energetica	Energi klass	Klasa energetyczna	Energiatõhususe klass	Klassi tal-effiċjenza fl-użu tal-enerġija	Класс эффективности использования энергии	
Classe d'efficacité énergétique	Κλάση ενεργειακής απόδοσης	Třída energetické účinnosti	Razred energetske učinkovitosti	Aicme éifeachtúlachta fuinnimh	Energiatohokkuusluokka	Energieeffektivitetsklasse	
Energie-efficiëntieklasse	Classe de eficiencia energética	Trieda energetickej účinnosti	Клас на енергийна ефективност	Energoefektivitātes klase	Enerji verimlilik sınıfı	Клас ефективності енергоспоживання	
Clase de eficiencia energética	Energieeffektivitetsklasse	Energiahatékonyasági osztály	Clasă de eficiență energetică	Energijos vartojimo efektyvumo klasė	Klasa energetske učinkovitosti		
Jahresstromverbrauch *2	Consumo annuale di energia elettrica *2	Årlig strömförbrukning *2	Zużycie prądu w skali roku *2	Aastane voolubrimus *2	Konsum annwali tal-elettriku *2	Годовое потребление электроэнергии *2	
Consommation d'électricité annuelle *2	Ετήσια κατανάλωση ρεύματος *2	Roční spotřeba elektrické energie *2	Letna poraba elektrike *2	Ídúi leicreachais bhliantúil *2	Vuotuinen sähkökulutus *2	Årlig strömforbruk *2	
Jaarlijks elektriciteitsverbruik *2	Consumo anual de electricidade *2	Ročná spotreba elektriny *2	Годишна консумация на електроенергия *2	Gada elektroenerģijas patēriņš *2	Yıllık elektrik tüketimi *2	Річне споживання електроенергії *2	
Consumo anual de electricidade *2	Årligt elförbruk *2	Éves áramfogyasztás *2	Consum anual de electricitate *2	Metinis elektros energijos suvartojimas *2	Godišnja potrošnja električne energije *2		
Lastauslegung	Carico nominale	Dimensionerande belastning	Maksimalne obciążenie	Projekteeritud koormus	Tagħbiya tad-disinn	Расчетная нагрузка	
Charge de calcul	Σχεδιασμός φόρτωσης	Jmenovité zatížení	Nazivna obremenitev	Lõd deartha	Laskettu kuormitus	Utformingsbelastning	
Ontwerpbelasting	Carga nominal	Projektované zaťaženie	Проектен товар	Aprējina slodze	Tasarim yükü	Розрахункове навантаження	
Carga de diseño	Brukslast	Méretezési terhelés	Sarcinā nominalā	Projektiņa aprkova	Težina uredaja		
Heizung (Durchschnitt / Wärmer / Kälter / Jahreszeit)	Riscaldamento (Stagione media / calda / fredda)	Värme (Genomsnittlig/varmare / kallare årstid)	Ogrzewanie (umiarkowane / cieplejsze / zimniejszy / sezonowe)	Kütmine (keskmise/soojem/külmemise periood)	Tishin (Medju / Aktar shun / Aktar kiesah / stagun)	Нагрев (средний/теплый/холодный сезон)	
Chauffage (Moyenne / Plus chaud / Plus froid / saison)	Θέρμανση (Μέση / υψηλότερη / χαμηλότερη θερμοκρασία)	Topení (průměrná/teplá/studená sezóna)	Ogrjevanje (povprečni/toplejši/hladnejši letni čas)	Téamh (Meánteoht / Níos Teo / Níos Fuairé / séasúr)	Lämmitys (Välkkaus / lämmin kausi / kylmä kausi)	Варме (Middels / Varmere / Kaldere / årstid)	
Verwarming (gemiddeld seizoen / warmer seizoen / kouder seizoen)	Aquecimento (Média estação / Estação mais quente / Estação mais fria)	Kúrenie (priemerné/teplejšie/chladnejšie obdobie)	Отопление (Средно / Топъл / Студен сезон)	Sildíšana (vidēji siltā/siltā/aukstā gadalaika)	Istma (Ortalama / Daha sıcak / Daha soğuk / mevsim)	Опалення (у середній/теплій/холодний сезон)	
Calefacción (temporada promedio / temporada más cálida / temporada más fría)	Opvarmning (genomsnittlig/varmere/koldere/sæson)	Fűtés (átlagos/melegebb/hidegebb évszak)	Încălzire (Anotimp normal/mai cald/mai rece)	Šildymas (vidutinis / šiltesnis / šaltesnis / sezoninis)	Grijanje (prosječno / toplije / hladnije / sezona)		
Nennkapazität	Capacità dichiarata	Deklarerad kapacitet	Deklarovaná pojemność	Deklarēritud vōimsus	Kapaċità ddiċjarata	Гарантированная мощность	
Capacité déclarée	Δηλωμένη χωρητικότητα	Udáváná kapacita	Prijavljena zmogljivost	Toileadh fógartha	Ilmoitettu teho	Erklært kapasitet	
Aangegeven capaciteit	Capacidade declarada	Deklarovaný výkon	Объявённая мощность	Deklarētā jauda	Beyan edilen kapasite	Гарантована потужність	
Capacidad declarada	Erklæret kapacitet	Névlages teljesítmény	Declarată declarată	Deklaruotasis pajėgumas	Deklarirani kapacitet		
bei angegebener Referenztemperatur	alla temperatura di progetto di riferimento	vid dimensionerande referenstemp-eratur	w znamionowej temperaturze odniesienia	projekteerimise võrdlustemperatu-uri juures	l'temperatura tad-disinn ta' referenza	при эталонной расчетной температуре	
à la température de calcul de référence	σε θερμοκρασία σχεδιασμού αναφοράς	při referenční výpočtové teplotě	ob referenčni nazivni temperaturi	ag teocht deartha tagartha	perusmitoitusalmpötilassa	ved referansetemperatur for utforming	
bij referentieontwerptemperatuur	a temperatura de diseño de referencia	pri referenčnéj výpočtovej teplote	pri izračunovani projektne temperatura	aprējina references temperatūrā	referans tasarim sıcaklığında	При эталонній розрахунковій температурі	
a temperatura de diseño de referencia	bei bivalenter Temperatur	alla temperatura bivalente	vid bivalent temperatur	w temperaturze bivalentnej	bivalentse temperatuuri juures	f'temperatura bivalenti	при бивалентной температуре
à température bivalente	à température bivalente	pri bivalentní teplotě	pri bivalentni temperaturi	ag teocht dhéifíúsach	kaksiarvoisessa lämpötilassa	ved bivalent temperatur	
bij bivalente temperatuur	a temperatura bivalente	pri bivalentnej teplote	pri бивалентна температура	bivalentā temperatūrā	iki deęerli sıcaklıkta	При бивалентній температурі	
a temperatura bivalente	bei Temperatur an der Betriebsgrenze	alla temperatura limite di funzionamento	vid driftstemperaturens gränsvärde	w granicznej temperaturze roboczej	tõotamise piirtemperatuuri juures	f'temperatura tal-limitu tat-tħaddim	при предельной рабочей температуре
à température de fonctionnement limite	σε θερμοκρασία ορίου λειτουργίας	při teplotě na hranici provozního limitu	pri mejni delovni temperaturi	ag teocht teorann oibriúcháin	toimintarajalämpötilassa	ved temperatur for driftsgrense	
bij grens werkingstemperatuur	a temperatura límite de funcionamiento	pri hranične prevádzkovej teplote	pri гранична работна температура	ekspluatācijas robežtemperatūrā	çalışma limiti sıcaklığında	При граничній робочій температурі	
a temperatura límite de funcionamiento	Backup-Heizleistung	Capacità di riscaldamento addizionale	Kapacitet för reservvärme	Zapasowa pojemność grzewcza	Tagavara küttevõimsus	Kapaċità tat-tishin ta' sostenn	Резервная тепловая мощность
Capacité de chauffage d'appoint	Δυνατότητα εφεδρικής θέρμανσης	Kapacita záložního vytápění	Rezervna zmogljivost ogrevanja	Toileadh téimh chúltaca	Varalämmitysteho	Sikkerhetskapasitet for oppvarming	
Reserveverwarmingscapaciteit	Capacidade de aquecimento de reserva	Výkon záložného vykurovacieho telesa	Мощност на спомогателно електрическо подгряване	Rezerves sildītāja jauda	Yedek ısıtma kapasitesi	Резервна тепла потужність	
Capacidad de calefacción auxiliar	Reservevermekaapacitet	Kiségítő fűtési teljesítmény	Capacitate de încălzire de siguranță	Pagalbinio šildymo pajėgumas	Kapacitet rezervnog grijanja		





**PRODUCT INFORMATION (\*1)**

ROOM AIR CONDITIONER	INDOOR MODEL	MSZ-FT35VG / MSZ-FT35VGK
	OUTDOOR MODEL	MUZ-FT35VGHZ

Function (indicate if present)	
cooling	Y
heating	Y

If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.	
Average (mandatory)	Y
Warmer (if designated)	Y
Colder (if designated)	Y

Item	symbol	value	unit
<b>Design load</b>			
cooling	Pdesignc	3.5	kW
heating/Average	Pdesignh	4.0	kW
heating/Warmer	Pdesignh	2.2	kW
heating/Colder	Pdesignh	5.9	kW

Item	symbol	value	unit
<b>Seasonal efficiency</b>			
cooling	SEER	8.6	-
heating/Average	SCOP/A	4.6	-
heating/Warmer	SCOP/W	5.8	-
heating/Colder	SCOP/C	3.5	-

<b>Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj</b>			
Tj=35°C	Pdc	3.5	kW
Tj=30°C	Pdc	2.6	kW
Tj=25°C	Pdc	1.7	kW
Tj=20°C	Pdc	1.3	kW

<b>Declared energy efficiency ratio, at indoor temperature 27(19) °C and outdoor temperature Tj</b>			
Tj=35°C	EERd	3.9	-
Tj=30°C	EERd	6.2	-
Tj=25°C	EERd	10.5	-
Tj=20°C	EERd	16.8	-

<b>Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj</b>			
Tj=-7°C	Pdh	3.6	kW
Tj=2°C	Pdh	2.2	kW
Tj=7°C	Pdh	1.5	kW
Tj=12°C	Pdh	0.9	kW
Tj=bivalent temperature	Pdh	4.0	kW
Tj=operating limit	Pdh	3.4	kW

<b>Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj</b>			
Tj=-7°C	COPd	2.9	-
Tj=2°C	COPd	4.6	-
Tj=7°C	COPd	5.9	-
Tj=12°C	COPd	6.7	-
Tj=bivalent temperature	COPd	2.6	-
Tj=operating limit	COPd	1.8	-

<b>Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj</b>			
Tj=2°C	Pdh	2.2	kW
Tj=7°C	Pdh	1.5	kW
Tj=12°C	Pdh	0.9	kW
Tj=bivalent temperature	Pdh	2.2	kW
Tj=operating limit	Pdh	3.4	kW

<b>Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature Tj</b>			
Tj=2°C	COPd	4.6	-
Tj=7°C	COPd	5.9	-
Tj=12°C	COPd	6.7	-
Tj=bivalent temperature	COPd	4.6	-
Tj=operating limit	COPd	1.8	-

<b>Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj</b>			
Tj=-7°C	Pdh	3.6	kW
Tj=2°C	Pdh	2.2	kW
Tj=7°C	Pdh	1.5	kW
Tj=12°C	Pdh	0.9	kW
Tj=bivalent temperature	Pdh	4.0	kW
Tj=operating limit	Pdh	3.4	kW
Tj=-15°C	Pdh	4.4	kW

<b>Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature Tj</b>			
Tj=-7°C	COPd	2.9	-
Tj=2°C	COPd	4.6	-
Tj=7°C	COPd	5.9	-
Tj=12°C	COPd	6.7	-
Tj=bivalent temperature	COPd	2.6	-
Tj=operating limit	COPd	1.8	-
Tj=-15°C	COPd	2.0	-

<b>Bivalent temperature</b>			
heating/Average	Tbiv	-10	°C
heating/Warmer	Tbiv	2	°C
heating/Colder	Tbiv	-10	°C

<b>Operating limit temperature</b>			
heating/Average	Tol	-25	°C
heating/Warmer	Tol	-25	°C
heating/Colder	Tol	-25	°C

<b>Cycling interval capacity</b>			
for cooling	Pcycc	x	kW
for heating	Pcyh	x	kW
Degradation co-efficient cooling	Cdc	0.25	-

<b>Cycling interval efficiency</b>			
for cooling	EERcyc	x	-
for heating	COPcyc	x	-
Degradation co-efficient heating	Cdh	0.25	-

<b>Electric power input in power modes other than 'active mode'</b>			
off mode	P <sub>OFF</sub>	1	W
standby mode	P <sub>SB</sub>	1	W
thermostat - off mode	P <sub>TO</sub>	8	W
crankcase heater mode	P <sub>CK</sub>	0	W

<b>Annual electricity consumption</b>			
cooling	Q <sub>CE</sub>	142	kWh/a
heating/Average	Q <sub>HE</sub>	1216	kWh/a
heating/Warmer	Q <sub>HE</sub>	527	kWh/a
heating/Colder	Q <sub>HE</sub>	3453	kWh/a

<b>Capacity control (indicate one of three options)</b>			
fixed		N	
staged		N	
variable		Y	

<b>Other items</b>			
Sound power level (indoor/outdoor)	L <sub>WA</sub>	60/61	dB(A)
Global warming potential	GWP (*2)	675	kgCO <sub>2</sub> eq.
Rated air flow (indoor/outdoor)		786/2412	m <sup>3</sup> /h

Contact details for obtaining more information	MITSUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS 3-18-1, Oshika, Suruga-ku, Shizuoka 422-8528, Japan E-mail: melshierp@MitsubishiElectric.co.jp
--	---

(\*1) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No. 206/2012.

(\*2) This GWP value is based on Regulation(EU)No. 517/2014 from IPCC 4th Assessment Report.

For Regulation (EU) No. 626/2001, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.

**TECHNICAL DOCUMENTATION (1)**

ROOM AIR CONDITIONER	INDOOR MODEL	MSZ-FT35VG / MSZ-FT35VGK	280H*838W*229D (mm)
	OUTDOOR MODEL	MUZ-FT35VGHZ	714H*800W*285D (mm)

Function	
cooling	Y
heating	Y


The heating season	
Average (mandatory)	Y
Warmer (if designated)	Y
Colder (if designated)	Y

Capacity control	
fixed	N
staged	N
variable	Y

Item	symbol	value	unit
<b>Seasonal efficiency (2)</b>			
cooling	SEER	8.6	-
heating/Average	SCOP/A	4.6	-
heating/Warmer	SCOP/W	5.8	-
heating/Colder	SCOP/C	3.5	-

Energy efficiency class			
cooling	SEER	A+++	-
heating/Average	SCOP/A	A++	-
heating/Warmer	SCOP/W	A+++	-
heating/Colder	SCOP/C	A	-

Other items			
Sound power level (indoor/outdoor)	L <sub>WA</sub>	60/61	dB(A)
Refrigerant	-	R32	-
Global warming potential	GWP (3)	675	kgCO <sub>2</sub> eq.

identification and signature of the person empowered to bind the supplier	
	Tadashi Saito Department Manager, Quality Assurance Department MITSUBISHI ELECTRIC CONSUMER PRODUCTS(THAILAND) CO.,LTD

(1) This information is based on COMMISSION DELEGATED REGULATION (EU)No. 626/2011.

(2) SEER/SCOP values are measured based on EN 14825:2016: Testing and rating at part load conditions and calculation of seasonal performance.

(3) This GWP value is based on Regulation(EU)No. 517/2014 from IPCC 4th Assessment Report.

For Regulation (EU) No. 626/2001, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.